Development of Standard Technology for In-service Test

Soon Joon Hong^a, Young Wook Chung^a, Byung Chul Lee^a, Gang Il Choo^b, Kang Deok Rhee^b, Taek Soo Youm^b, Kyung Hoon Lee^b, Jin Ho Kim^b, Kwang Sik Choi^b, Dong Jin Lee^b, Ho Jin Jung^b, In Sam Hwang^b, Bong Baek Kim^b, Jae Won Lee^b, and Soo Gil Lee^c

^a FNC Technology Co., Ltd., SNU RPIC #516, San 4-2 Bongchun7-dong, Gwanak-gu, Seoul 151-818, Republic of Korea

sjhong90@fnctech.com

^b Korea Hydro & Nuclear Power Co., Ltd ^c Hanvit Power Service

1. INTRODUCTION

Nuclear power plant has several safety features and each safety feature is based on the operation of pumps and valves. Thus, it is an essential basis for the safety of nuclear power plant to keep operational readiness of pumps and valves. Technology Rule 63.1.2 of Nuclear Facility etc. requires In-service Test (IST) for pumps and valves.

Our domain nuclear power plants can be classified into

- 1) Westinghouse 2 Loop (PWR600)
- 2) Westinghouse 3 Loop (PWR900)
- 3) Framatom 3 Loop
- 4) Korea Standard Nuclear Power Plant (KSNP)
- 5) CANDU

Each type of plant has similar design and maintenance features. However, the IST program in each type is slightly different each other in components subjected to IST, test item, test period and so on. These have caused excessive effort for the test itself, the response to regulatory authority, and the response to the change of code and standards.

This study is motivated in order to resolve such problems as a first step. The objectives of this study is

- 1) Development of standardization methodology of IST for each plant type
- 2) Development of IST technical backgrounds for each plant type
- 3) Development of standard IST plan on the base of the technical backgrounds for each plant type

The results of this study will be utilized in

- 1) Effective response for the regulatory activities using the standard technical backgrounds and plan for IST
- 2) Exclusion of none-safety functioned components from the definite analysis for each component

3) Foundations for the relief request

Because of practical status in each plant, the concerned plants are limited to: 1) KSNP (YGN3&4, YGN5&6, UCN3&4, UCN5&6), 2) PWR900 (Kori3&4, YGN1&2), 3) CANDU

2. APPROACH TO STANDARD TECHNOLOGY

2.1 Code and Standards

The first code and standard is Ministry of Science and Technology (MOST) Guide 2004-14[1]. This guide

identifies the requirement of IST, and endows KEPIC MO 2000 [2] or ASME OM 1995 and its addenda [3] for detailed test requirements. KEPIC MO 2000 is also based on ASME OM 1995 and its addenda. KINS-G-018 (Rev.1) is also used as a code and standards [4]. NUREG-1482 (Rev.1) is referred to as complementary code and standards[5].

2.2 Standardization Methodology

Standardization for each type of plants was carried out according to following procedures

- 1) List up the components subjected to technical background according to reference format
- 2) Consolidate the lists for each type of plant
- 3) Review the function of the components
- 4) Decide the safety function of each components
- 5) Review the test items, frequency and so on
- 6) Comments on the difference between units for each type of plant

3. DEVELOPMENT OF TECHNOLOGY BACKGROUND FOR IST

The references for selecting the components subjected to technical background are current IST plan, FSAR Ch. 3, FSAR Ch. 6, FSAR Ch. 16, Emergency Operation Procedure (EOP), Probabilistic Safety Analysis (PSA) reports, Engineer Safety Feature (ESF) components, Safety Class components, and components of regulatory authority requirement.

Technical background is made in MS-Excel and Hangul word. Samples are shown in Figs. 1 and 2.

As a result the number of components subjected to technical background is

- 1) KSNP : Pump 43, Valve 886
- 2) PWR900 : Pump 35, Valve 708
- 3) CANDU : Pump 34, Valve 475

4. DEVELOPMENT OF STANDARD IST PLAN

IST plan of each plan was reviewed for standardization. At first standard form IST plan was composed regardless of plant type. And then specific features for specific plant type were reflected in the IST plan for each type. There was not significant difference in body of IST plan. The detailed items were attached in appendix.

5. RELIEF REQUEST

MOST Guide 2004-14 allows relief request for the components which are very hard to test or test of which results in reverse effect in overall plant safety. In this study current relief requests of each plant are integrated. Some foreign relief request was also integrated. All these cases were classified according to its request type. Such a classification will helpful in further relief request in each plant to both licensee and regulatory authority. The results are summarized in Table 1. Foreign cases shows variety of relief request for domain plan may be possible in future.

6. CONCLUSION

From this study following outputs were generated

- 1) Standard IST plan
- 2) Standard technical background for each plant type
- 3) List of components subjected to technical background

These outputs can be used as first reference for further


development of IST plan in each plant. And these also can provide the technical background for regulatory authority.

This study is the first attempt for the systematic IST program, and continuous technical meeting among plants is needed for the better IST program. Such activities may produce grand standardization for IST, which means the standardization for all domain nuclear power plant.

REFERENCES

- MOST Guide 2004-14, Guide for In-service Test of Safety-related Pumps and Valves, Ministry of Science and Technology (MOST), 2004
- [2] KEPIC MO, In-service Test for Nuclear Power Plants, 2000
- [3] ASME OM, Code for Operation and Maintenance of Nuclear Power Plants, 1995
- [4] D.Y. Cho, et al, Guidelines for In-service Test for Safety Related Pumps and Valves, KINS/G-018 Rev.1
- [5] Steven M. Unikewicz, Guidelines for Inservice Testing at Nuclear Power Plants, NUREG-1482 Rev.1

			별브 구분				연평 시	1월 요리	년 (물건	932/	- 진21	1/영광	3增/5	(평2별					: तम	요견 문	ą				밸브 시점 기술배경		L			KS	es.	IST 4	생	보시	명 표	봐 (안)	
전치 순빈	718	보 호 변 빈	명 년 년	가면 왕년	클브 크기 (*)	비주) 1 주 1 주	월 드 작동 상태	사 7동 정 명식 위	양 중상 인 비치 위	전 3 1치	(2)시 물 2	8 장목 8 3	이시 위 2	. 0 명 밝힌 지 조	소전	FSAR 8 3	3장 물 8 2 2	物の	FSAR 영 월 3 2	68 8 2	TY PE 'C'	T / S	밸브 기능	안전성 수행 여부 평가 [녕각제 압력경계의 간전성 투지, 원자로의 안전정 지, 정지상태의 듣지 또는 사고결과를 완화시키는 기 능]	기 티아 일차지 내에지 일쓰기공 내장 쉬부	주 야 도 제	CLI OR L'À L'O	2 02 IE M	20 10 10	가 등 장 경	정상위치	- 11	시 원 장 북	平	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	2
1	RC	V101	PZR SDS lao W	9-431- 002	4	в 1	G	88	wo i	c	D F C Z	FZ	FZ	F F Z F			0 0	o c	-		1		- 5	OPEN : 급수완전상실시고시 가입기 안전별브 개방 이후 RCS 압력을 고압안전주입행프 주입압력하지 낮추기위해 사용형. CLOSE : 정상운전용 닫림 상태를 뮤지	설계기준사고를 초려하는 급수완전상실시고시에 RCS 입려를 감압, 안전우업이 가능하도록 하여 사고 결과를 완하시키는데 필요한 필수 실비임 [FSAR 3장]	2 - 0 0	в	1	G	88	мо	с	0	FZ	R R	9 9 양방장시원	1 † 8
2	RC	V102	PZR SDS lao W	9-431- 002	4	в 1	G	88	wo i	c	D F C Z	FZ	FZ	F F Z F			0 0	o c	-		-		- 5	OPEN : 급수완전상실시고시 가입기 안전별브 개방 이후 RCS 압력을 고압안전추입행프 주입압력하지 낮추기위해 사용형. CLOSE : 정상운전용 닫림 상태를 뮤지	설계기준사고를 초려하는 급수완전상실시고시에 RCS 입려를 감압, 안전우업이 가능하도록 하여 사고 결과를 완하시키는데 필요한 필수 실비임 [FSAR 3장]	2 - 0 0	в	1	G	58	мо	с	0 C	FZ	R R	9 양방장시원	1 † 8
3	RC	V103	PZR SDS CTRL W	9-431- 002	4	A 1 B	۱a	68	wo i	c	D LFZ	L F Z	L F Z	FZ			0 0	o c	-		-		- 5	낮추기위해 사용됨.	RCS 압력을 감압, 안전추입이 가능하도록 하여 사고 결과를 완화시키는데 필요한 필수 설비의,	2 - 0 0	٨	1	L	88	мо	с	0 0	L F Z	R R	9 9 양방장시원 9	1 † 8



₫ : P10.	J		개경 번호 :	0 (2005. 12. 51).
프 계요.	I.			
7 £.	운전 δ.6 호기↓	영광 5,6 호기 🔳	욷곈 5.4 호기 ↓	영광 5.4호기 🌙
8 3 5 5 1	1차기기 넘斗	1차기기 넘자	1차기기 넘자	1차기기 넘각
6-2 - 3 +9	히수 펌프 🔒	히수 평드 🕽	해수 평드 🤳	해수 평드 🕽
	SX-PP01AJ	SZ-PP01A J	SX-PP01A J	SX-01FA J
≜ শাহ	SX-FP02A	SX-PP02A J	SX-PP02A J	SX-02FA J
6 U.S.	SX-PP0 1B 🜙	SX-FF01B 🤳	SX-FF01B J	SX-01FB J
	SX-PF02B 🤳	SX-FF02B J	SX-FF02B J	SX-02FB J
화고 도면	9-462-N176-001	9-462-N176-001	9-462-N176-001	9-462-N176-001
	수리장축원심평트.	수직장축원심평트.		수직장축원심평프.
반전 둥급	5 <mark>. 1</mark>	5,	5.	ឹ 🎝
또 규제요 운격 5.6		PSAR 5장, 8기, 운영 54, 18	기 913-5457	T/S.J
프 규제요 울 집 5.6 N/A	호기 영瑞 5.6 :	6기. 운전 5.4 호	기 <mark>니 영광 5,4호</mark> 기 N/A J	ر گر T ل ا
물건 5.6 N/A 모든 기 능, 모든 운작 전생 행기 1차 기기 를 완화 5 중 시험 · 전용 대·	고기. 영국 6.6 3 고 N/A - 이모드에서 1값을 인 나 내 입자하수 챔프의 7 서키는 안전기능 수 수백 여분 : YES, 출 효기 : 영국 8.4	<u>학가, 문</u> 철 8.4 호 · N/A J · N/A 의 · N/A 의 · N/A 의 · N/A 의 · N/A 의 · · · · · · · · · · · · · · · · · · ·	N/A J 의 최종 별겠건됐으 전접지, 접지상태의	▲ 이 · · · · · · · · · · · · · · · · · ·
응 기 6.6 N/A 모든 기 등 나 전 4 평기 1 자 기기 문 완화 5 중 4 월 · 전용 월	고 위작 6.6 3 고 위작 6.6 3 고 N/A 대 대 대 대 대 대 대 대 대 대 대 대 대	2 7. 문접 8.4 호 · N/A J 1국 및 비안재기기: 1 등은 웹가트의 안 웹 J j 호기, 움직 8.4호기	의 취종 옆겠건였으 전점기, 접지상태의 , 영향 5,6호기, 음	○」 ○」 ○」 第月 또는 사고계 집 6,8호기」
물건 5.6 N/A 모든 기 능, 모든 운작 전생 행기 1차 기기 를 완화 5 중 시험 · 전용 대·	고기. 영국 6.6 2 고 N/A - 모드드에서 1값을 인 나가 다 관리 가 하는 안 나가 는 안전기는 우 나가 는 안전기는 우 수 에 여분 : YES., 삼 호기 : 영광 8.4 프 시험 포근 #	<u>27] </u>	의 취종 코쳐건렸으 가격기, 경기상태의 , 영광 5,6호기, 음	○」 ○」 ○」 第月 또는 사고계 집 6,8호기」
응 기 6.6 N/A 모든 기 등 나 전 4 평기 1 자 기기 문 완화 5 중 4 월 · 전용 월	고기. 영국 6.6 3 고 N/A - 비모드에서 1차운 역 너가비수 행트의 7 내가비수 행트의 7 내가비수 행트의 7 내가비수 행트의 7 나기는 안재기능 수 수택 여분 : YES, 출 호기 : 영광 8.4 프 시험 포근용 : 시 인 관 문	2 7. 	의 취종 옆겠건였으 전점기, 접지상태의 , 영향 5,6호기, 음	○」 ○」 ○」 第月 또는 사고계 집 6,8호기」

	0	
Table 1	Classification	of Relief Request

	Pum	np	
Reference	Relief Request	Basis for Relief Request	Number
Acceptance criteria	Changing alert range	Operability proved by baseline vibration study and monitoring	Foreign :2
Operation point	New operation point or new pump curve	Impossible to operate at reference	Foreign :3
Measurement	Not measure flow rate, differential pressure, or vibration	Impossible to install the sensor	Foreign :12 Domain : 1
Test accuracy	Full scale change	Provide basis for sufficient safety level	Foreign :2
	Check	Valve	
Reference	Relief Request	Basis for Relief	Number
Sampling Method	Testing for sampled valves in refueling outage	Operability proved by sampling program	Foreign : 6 Domain : 2
Extension of Test Period	Delay test to cold shutdown or refueling outage	Avoiding retardation of EDG operability, etc.	Foreign : : Domain :
Non-intrusive Test	Non-intrusive testing for sampled valves	No indicator, differential pressure meter	Foreign : 2
Monitoring Program	Applying the check valve monitoring program	Provide basis for sufficient safety level	Foreign :
Non-safety Direction Closure	Relief for close direction full stroke test	Close direction is non-safety position	Domain :
	Group A&	B Valve	
Reference	Relief Request	Basis for Relief	Number
Measurement	Not measure stroke time	Impossible to install the sensor	Foreign : Domain :
Other Test Program	Endow to MOV Test Program	Provide basis for sufficient safety level	Foreign :
	Relief	/alve	
Reference	Relief Request	Basis for Relief	Number
Thermal Equilibrium	Not evaluate the thermal equilibrium	Inadequate to evaluate the thermal equilibrium	Foreign :
Set Pressure of Valve	Not use the accumulator volume	Accumulator volume is not needed to establish the set pressure	Foreign :

-7. 완희요계.

Fig.2 Hangul Form of Technical Background