

## Fabrication of small mock-ups for the KO HCCR TBM

Jae Sung Yoon<sup>a\*</sup>, Suk-Kwon Kim<sup>a</sup>, Eo Hwak Lee<sup>a</sup>, Hyung Gon Jin<sup>a</sup>, Dong Won Lee<sup>a</sup>, Seungyon Cho<sup>b</sup>

<sup>a</sup>Korea Atomic Research Institute, Daejeon, Republic of Korea

<sup>b</sup>National Fusion Research Institute, Daejeon, Republic of Korea

\*Corresponding author: jsyoon2@kaeri.re.kr

### 1. Introduction

To develop next-generation technologies, one of the important objects of the ITER project is to investigate the heat extraction from the blanket module in a fusion reactor and tritium extraction experiments [1-7]. Korea has decided to test a helium cooled ceramic reflector (HCCR) test blanket module (TBM) in ITER [8]. The HCCR TBM is composed of four sub-modules and a back manipulator (BM). The fabrication technologies for HCCR TBM have been developed through the development of welding and joining technologies [9-13]. In addition, an advanced reduced activation alloy (ARAA) material has been developed and characterized for the HCCR TBM as a structural material, and used for a fabrication of the TBM mock-up. In a previous study, the fabrication method of the first wall was developed along with a half-scale mock-up using SS316L steel through a fabrication procedure [13].

In the present study, the fabrication procedure of the breeding zone including the side wall and a sub-module are introduced. Four small mock-ups were designed and fabricated to verify the fabricating procedure and method of the HCCR TBM sub-module. A distortion measurement using a distortion dial gage and gamma ray radiographic test to confirm the distortion rate after E-beam welding and joint integrity were carried out.

### 2. Fabrication procedure of the HCCR TBM sub-module and fabrication of small mock-up

#### 2.1 Design and welding conditions of the small mock-ups

Four small mock-ups were designed and fabricated to verify the fabricating procedure and method of the HCCR TBM sub-module. Figure 1 shows the HCCR sub-module and breeding zone of the sub-module and four parts components marked with circles for manufacturing.

The small mock-ups in Fig. 2 show parts of the scaled-down sub-module. Part-A is a part of the scaled-down FW of a front plate with two cooling channels of 11 mm in width; Part-B is composed of two parts of the BZ components to verify the welding procedure; Part-C is composed of three parts of the BZ, SW of 25 mm thickness, and SW cover of 5 mm thickness; and Part-D is composed of FW, SW, and BZ components of 25 mm

thickness plates. The small mock-ups have been designed. In addition, the E-beam and laser beam weld were carried out to optimize the welding procedure considering the weld speed and current to optimize the fabrication using ARAA plates from 5 mm to 25 mm in thickness.




Fig. 1. Schematic diagram of HCCR TBM




Fig. 2. Schematic diagram of the small mock-up

### 2.2 Fabrication of the small mock-ups

The manufacturing procedure of the HCCR TBM mock-up is as follows: 1) component machining, 2) welding, 3) post-machining, 4) NDT testing using radiography test (RT), and ultrasonic testing (UT). Hence, a leakage test, water pressure test, and so on will be carried out. Figs. 3 and 4 show the detailed manufacturing process. Figure 3 shows Part-B, which is BZ component of 5 mm thickness by E-beam welding. The fabrication procedure of BZ was processed as follows: first, the side plates were attached to each other, second, the E-beam weld was carried out at the top and bottom regions, third, the component was machined, and fourth, the E-beam weld was conducted in the side region again. Figure 4 shows Part-C, which is the fabrication of the BZ and SW, and was processed as follows: first, BZ and SW were machined, and second, E-beam welding was carried out.




Fig. 3. Schematic diagram of the manufacturing process of the small mock-up of BZ (Part B)




Fig. 4. Schematic diagram of the manufacturing process of the small mock-up of FW-SW-BZ (Part C)

### 2.3 Radiography test and distortion measurement

After E-beam weld and laser beam weld for the small mock-ups, gamma ray radiographic tests were carried out to investigate joint integrity. In addition, to verify the distortion after the E-beam weld, the amount of distortion was investigated using a distortion test dial gage. Figure 5 shows the measurement points of distortion in BZ small mock-up. The maximum distortion is -0.06 mm at the upper right and lower left edge regions, but can be an acceptable value.

To investigate the defect at the welding position of the small mock-up of FW-SW-BZ (Part C), the gamma ray radiographic test was carried. Figure 6 shows a photograph of the RT test result of the small mock-up of the FW-SW-BZ (Part-C), and it shows that there is no defect in the mock-up of FW-SW-BZ clearly. In addition, severe deformations are also not found in the RT test.




Fig. 5. Distortion measurement position in BZ side wall region




Fig. 6. Result of RT test in FW-SW-BZ region

### 3. Conclusions

A fabrication procedure for the manufacturing of the HCCR TBM sub-module was performed and small mock-ups were fabricated using an E-beam and laser beam weld to verify the manufacturing procedure and method of the HCCR TBM sub-module. To establish and optimize the welding procedure in an E-beam weld from ARAA material, the distortion and radiographic tests were carried out from the E-beam weld results. It could be noted that a small amount of distortion occurred, but the values are small enough to neglect for the fabrication. In addition, a helium leak test and water pressure test will be performed for verification of the fabricated small mock-ups.

### Acknowledgments

This work was supported by a National Research Foundation of Korea (NRF) grant funded by the Ministry of Science, ICT and Future Planning of the Republic of Korea (NRF-2015M1A7A1A01002474).

### REFERENCES

- [1]L.M. Giancarli, M. Abdou, D.J. Campbell, V.A. Chuyanov, M.Y. Ahn, M. Enoeda et al., Overview of the ITER TBM Program, *Fusion Engineering and Design* 87, (2012) 395-402.
- [2]E. Rajendra Kumar, T. Jayakumar, A.K. Suri, Overview of TBM R&D activities in India, *Fusion Engineering and Design* 87, (2012) 461-465.
- [3]M. Enoeda, H. Tanigawa, T. Hirose, S. Suzuki, K. Ochiai, C. Konno et al., Development of the Water Cooled Ceramic Breeder Test Blanket Module in Japan, *Fusion Engineering and Design* 87, (2012) 1363-1369.
- [4]K.M. Feng, C.H. Pan, G.S. Zhang, T.Y. Luo, Z. Zhao, Y.J. Chen et al., Progress on design and R&D for helium-cooled ceramic breeder TBM in China, *Fusion Engineering and Design* 87, (2012) 1138-1145.
- [5]A.Yu. Leshukov, V.K. Kapyshev, I.A. Kartashev, V.G. Kovalenko, A.V. Razmerov, M.N. Sviridenko et al., Overview of Russian Federation activity on the LLCB TBM design and analysis, *Fusion Engineering and Design* 87, (2012) 1487-1494.
- [6]G. Aiello, G. de Dinechin, L. Forest, F. Gabriel, A. Li Puma, G. Rampal et al., HCLL TBM design status and development, *Fusion Engineering and Design* 86, (2011) 2129-2134.
- [7]C.P.C. Wong, M. Abdou, M. Dagher, Y. Katoh, R.J. Kurtz, S. Malang et al., An overview of the US DCLL ITER-TBM program, *Fusion Engineering and Design* 85, (2010) 1129-1132.
- [8]S. Cho, M.Y. Ahn, D.W. Lee, Y.H. Park, E.H. Lee, J.S. Yoon et al., Overview of Helium Cooled Ceramic Reflector Test Blanket Module development in Korea, *Fusion Engineering and Design* 88, (2013) 621-625.
- [9]J.S. Yoon, S.K. Kim, E.H. Lee, S. Cho, D.W. Lee, Fabrication of a 1/6-scale mock-up for the Korea TBM first wall in ITER, *Fusion Science and Technology* 62 (2012)29-33.
- [10]Y.B. Chun, C.H. Han, B.K. Choi, K.B. Kim, S.H. Kang, S.H. Noh, et al., Effects of alloying elements and heat

treatment conditions on mechanical properties of reduced activation ferritic-martensitic steel, in: 16th International Conference on Fusion Reactor Materials, Beijing, China, October 20-26, 2013.

[11]S. Cho, D.H. Kim, M.Y. Ahn, Development of low activation ferritic/martensitic steel welding technology for the fabrication of KO HCSB TBM, *Journal of Nuclear Materials* 386-388 (2009) 491-494.

[12]J.S. Lee, J.Y. Park, B.K. Choi, B.G. Hong, K.J. Jung, Y.H. Jeong, HIP joining of RAFM/RAFM steel and beryllium/RAFM steel for fabrication of the ITER TBM first wall, *Metals and Materials International* 15 (2009) 465.

[13]J.S. Yoon, S.K. Kim, E.H. Lee, S. Cho, D.W. Lee, Fabrication and integrity testing of a Korean ITER TBM FW mock-up in preparation for high heat flux test, *Fusion Science and Technology* 64 (2013) 657-661. J.S. Yoon et al.,